



Qingdao Zongjin Engineering Machinery Co.,Ltd.

ADD: #1115, International Business Center , NO.196 Zhengyang Rd , Chengyang , Qingdao , China

<http://www.chinawheelloaders.com>

E-mail:[info@chinawheelloaders.com](mailto:info@chinawheelloaders.com)

Tel:0086-532-66739792

Fax:0086-532-66739791

## Specification of ZL10 wheel loader



### Performance and characteristic

- I、 Streamlined appearance, beautiful and elegant.
- II、 Fully hydraulic steering system, easier operation.
- III、 Bucket can be leveled automatically, high productivity.
- IV 、 Comfortable operation environment, new design cabin, air-conditioner at option.
- V、 Various working devices of attachment are available, such as wooden fork, pipe fork, grass fork, stone bucket, enlarged bucket, plow, fork etc, to meet different needs.



**Qingdao Zongjin Engineering Machinery Co.,Ltd.**

ADD: #1115, International Business Center , NO.196 Zhengyang Rd , Chengyang , Qingdao , China

<http://www.chinawheelloaders.com>

E-mail:[info@chinawheelloaders.com](mailto:info@chinawheelloaders.com)

Tel:0086-532-66739792

Fax:0086-532-66739791



www.chinawheelloaders.com





Qingdao Zongjin Engineering Machinery Co.,Ltd.

ADD: #1115, International Business Center , NO.196 Zhengyang Rd , Chengyang , Qingdao , China

<http://www.chinawheelloaders.com>

Tel:0086-532-66739792

E-mail:[info@chinawheelloaders.com](mailto:info@chinawheelloaders.com)

Fax:0086-532-66739791





**Qingdao Zongjin Engineering Machinery Co.,Ltd.**

ADD: #1115, International Business Center , NO.196 Zhengyang Rd , Chengyang , Qingdao , China

<http://www.chinawheelloaders.com>

E-mail:[info@chinawheelloaders.com](mailto:info@chinawheelloaders.com)

Tel:0086-532-66739792

Fax:0086-532-66739791





Qingdao Zongjin Engineering Machinery Co.,Ltd.

ADD: #1115, International Business Center , NO.196 Zhengyang Rd , Chengyang , Qingdao , China

<http://www.chinawheelloaders.com>

E-mail:[info@chinawheelloaders.com](mailto:info@chinawheelloaders.com)

Tel:0086-532-66739792

Fax:0086-532-66739791

<b>Specification</b>	<b>Overall Weight(Kg)</b>	<b>2850</b>
	<b>LxWxH(Mm)</b>	<b>4750x1500x2530</b>
	<b>Rated Bucket Capacity(M<sup>3</sup>)</b>	<b>0.5</b>
	<b>Rated Load(Kg)</b>	<b>1000</b>
	<b>Wheel Base</b>	<b>1985mm</b>
	<b>Track Base</b>	<b>1215mm</b>
	<b>Max.Breakout Force</b>	<b>22KN</b>
	<b>Maximum Dump Height (Mm)</b>	<b>2300mm</b>
	<b>Reach Fully Raised</b>	<b>850mm</b>
	<b>Bucket Width</b>	<b>1400mm</b>
	<b>Bucket Indicator</b>	<b>Yes</b>
	<b>Engine</b>	<b>Model</b>
<b>Rated Power(Kw)</b>		<b>37KW</b>
<b>Rated Speed(R/Min)</b>		<b>2200</b>
<b>Type</b>		<b>In-Line Arrangement, Water Cooled, Three-Cycle Diesel Engine</b>
<b>Engine Starting Mode</b>		<b>Electric</b>
<b>Brake Mode</b>	<b>Four-Wheel Hydraulic Spread-Shoed Brake</b>	
<b>Steering System</b>	<b>Type</b>	<b>Articulated And Hydraulic Steering</b>
	<b>Min Turning Radius(Mm)</b>	<b>4200</b>
	<b>Min.Ground Clearance</b>	<b>250mm</b>
<b>Tyres</b>	<b>Standard Tyres</b>	<b>1200-16</b>
	<b>Optional Tyres</b>	<b>14/90-16</b>